

















	Тип	Напряжение	Крутящий момент	Температура (допустимая температура окружающей среды)
	SA 07.1	400V, 50Hz 3~	30 Nm	-25 °C до80 °C
	SA 07.5	400V, 50Hz 3~	60 Nm	-25 °C до80 °C
	SA 10.1	400V, 50Hz 3~	120 Nm	-25 °C до80 °C
	SA 14.1	400V, 50Hz 3~	250 Nm	-25 °C до80 °C
	SA ExC 07.1	400V, 50Hz 3~	30 Nm	-20 °C до40 °C
	SA EXC 07.5	400V, 50Hz 3~	60 Nm	-20 °C до40 °C
	SA ExC 10.1	400V, 50Hz 3~	120 Nm	-20 °C до40 °C
	SA ExC 14.1	400V, 50Hz 3~	250 Nm	-20 °C до40 °C
	SAR 07.1	400V, 50Hz 3~	30 Nm	-25 °C до60 °C
	SAR 07.5	400V, 50Hz 3~	60 Nm	-25 °C до60 °C
	SAR 10.1	400V, 50Hz 3~	120 Nm	-25 °C до60 °C
	SAR 14.1	400V, 50Hz 3~	250 Nm	-25 °C до60 °C
	SAR ExC 07.1	400V, 50Hz 3~	30 Nm	-20 °C до40 °C
	SAR EXC 07.5	400V, 50Hz 3~	60 Nm	-20 °C до40 °C
	SAR ExC 10.1	400V, 50Hz 3~	120 Nm	-20 °C до40 °C
	SAR ExC 14.1	400V, 50Hz 3~	250 Nm	-20 °C до40 °C